



**POINTER**



Cellocator Division  
Pointer Telocation Ltd.

# CELLOCATOR™ 370-50 CATALOG & ACCESSORIES



**[sales@pointer.com](mailto:sales@pointer.com)**




**POINTER**





Cellocator Division  
Pointer Telocation Ltd.

## Cellocator™ 370-50 Catalog & Accessories

NAME	DESCRIPTION	PICTURE
<p><b>Cellocator™ 370-50 GS72030393D</b></p>	<p>The Cellocator™ 370-50 incorporates the features of the Compact Security with enhanced security capabilities such as multi IO ports and full alarm system capabilities.</p> <p>With hundreds of programmable parameters including various immobilization methods approved by insurance companies, incorporating car alarm features, advanced driver behavior analysis, tow detection, Geo-Fence, driver identification, accident detection, connection to MDT (Mobile Data Terminal), and interface with comfort car remote control.</p> <p>Utilizing GSM/GPRS and IP communication together with GPS technology ensures inexpensive, yet reliable communications together with efficient remote vehicle tracking.</p> <p>The Cellocator™ 370-50 offers security and fleet service providers and their customers with optimum solutions in coverage, lowest cost tracking, easy installation and limitless functionality.</p>	

### Complimentary Equipment





Harness			
NAME	DESCRIPTION	PART NUMBER	PICTURE
<p><b>Full Vehicle Harness</b></p>	<p>The full wiring harness, used for an installation of the Compact unit in the vehicle</p>	<p>711-00109F 711-00110</p>	
<p><b>HF Adaptor (Harness)</b></p>	<p>Harness, used for an installation of the Hands Free unit.</p>	<p>711-00197</p>	

## Cellocator™ 370-50 Catalog & Accessories

NAME	DESCRIPTION	PART NUMBER	PICTURE
Relay Set	A standard automotive relay (P/N: 711-20000) with its socket (P/N: 711-20023). Designed to adapt between unit's output and a device in the vehicle (immobilizer, siren etc).	711-20000 711-20023	
Fuse and Housing	Protective fuse (3Amp).	710-00001	
Distress Button	Push Button, used for connection to unit's input. Can serve as a distress button for example, or as a Voice call control button.	711-20001	
<b>Antennas</b>			
GPS receiver module	A standard Cellocator GPS receiver (SiRFIII chipset). Supplied with 3 meters cable, non-water resistant (dedicated for indoor installation). Can be supplied sealed (per request) Cable length can be supplied by request (standard 3m).	813-52A20	
External GSM Antenna	External GSM antenna with 3m cable.	701-10009	








## Cellocator™ 370-50 Catalog & Accessories






NAME	DESCRIPTION	PART NUMBER	PICTURE
<b>Back Up Battery</b>			
<b>Backup Battery</b>	6v, 1.2 Ah, sealed lead acid (SLA) backup battery.	711-20060	
<b>Accessories</b>			
<b>Cellocator™ Handsfree Kit</b>	A new Hands Free kit (delivering superior voice quality) bundled with a matching keypad enables I-Call (information), B-Call (breakdown) and E-Call (emergency) services delivered to fleets as well as car manufactures!	712-20016	
<b>Dallas Kit</b>	Coded keys with matching receiver that enable immobilizations and driver-recognition applications for both security and fleet services. Includes 2 keys and one cradle/reader.	712-20015	
<b>Siren SR 105A</b>	A siren, used for feedback and signaling.	711-20004	



## Cellocator™ 370-50 Catalog & Accessories




NAME	DESCRIPTION	PART NUMBER	PICTURE
Programming Cable		711-00006	
Vehicle Simulator Device (Tester)	This device simulates the basic activities that occur in a vehicle (like Door Open, Ignition On/Off and so on) and indicates the status of the vehicle's various devices (Siren, Blinkers and so on).	715-10000	
Simulator Cable	The wiring harness that connects the simulator device to the Cellocator unit. The harness provides an interface to every one of Cellocator unit's I/O and communication ports.	711-00111	
KeyLok USB Dongle (Software protection key)	KeyLok USB Dongle (Hardware Against Software Piracy) is a plug that connects to the testing computer's serial or USB port, protecting Cellocator's proprietary software and firmware against illicit use.	711-30015	
Pi Cable	This 4 connector pi-shaped cable is designed for troubleshooting the terminal modem side.	711-00009	

## Cellocator™ 370-50 Catalog & Accessories

NAME	DESCRIPTION	PART NUMBER	PICTURE
<b>Communication Logging Cable</b>	A "spy cable", which, together with the Cellocator Logger software records the activities of the unit's microcontroller and GSM modem, enabling troubleshooting.	711-00039	
<b>Adaptors for Communication Logging Cable</b>		711-00038	
<b>Signal Simulator</b>	Signal simulator is a tool designed to simulate vehicle alarm system. Used to test the correlation input feature of the unit.	715-11000	
<b>GPS Simulator Cable</b>	This cable is connected to the unit and the testing computer, and by means of the GPS simulator software (included) it emulates the activity of GPS navigation in a vehicle.	711-00051	
<b>USB to RS-232 Serial Adapter</b>	USB to RS-232 Serial Adapter allows data transfer from a USB port to a serial port whenever the computer does not have a conventional RS-232 9-pin serial port.	711-30016	



## Cellocator™ 370-50 Catalog & Optional Accessories

NAME	DESCRIPTION	PART NUMBER	PICTURE
<b>Optional Accessories</b>			
<b>MDT860</b>	Mobile Data Terminal, allowing text messaging with the driver. The MDT includes wire harness and a flexible suction windscreen mount.	715-32000	
<b>BT Adaptor</b>	A Blue Tooth adapter for unit's COM port, adding a BT interface to Cellocator unit.	K060-015	
<b>Enfora GSM1308 Terminal Modem Kit (optional)</b>	Terminal Modem kit is an optional component of the Cellocator's Evaluation Kit and should be ordered separately. This modem is to be connected to the PC serving as a Communication server for the purpose of establishing SMS communication with the unit or for initiating dialup connection to GPRS. The kit contains the modem, a cellular antenna, a power adaptor and a communication cable.	610-01308	





**POINTER**



Cellocator Division  
Pointer Telocation Ltd.

## Cellocator™ 370-50 Catalog & Optional Accessories

NAME	DESCRIPTION	PART NUMBER	PICTURE
<b>Sensors</b>			
<b>Temperature Sensor</b>	Enables temperature monitoring measurements in different compartments chilled.	AR-0187	
<b>Fuel Sensor</b>	Enables fuel monitoring consumption - connecting the analogue input of the devices.	AR-0184	
<b>Accident Sensor</b>	Enables accident/crash detection by triggering upon forward/backward impact of above 8g, or side impact of above 3g (adjustable sensitivity). Features false-alarm proof software.	711-20117	