



**POINTER**



Cellocator Division  
Pointer Telocation Ltd.

# COMPACT SECURITY CATALOG & ACCESSORIES



**[sales@pointer.com](mailto:sales@pointer.com)**






**POINTER**




Cellocator Division  
Pointer Telocation Ltd.

## Compact Security Catalog & Accessories

NAME	DESCRIPTION	PICTURE	
<b>Compact Security GT660007B-TR3N GE660007B-ER3N</b>	<p>The Cellocator™ Compact Security is an innovative integrated Car Alarm and fleet management unit with superior location, tracking, event driven reporting, logging, and security capabilities. Its uniquely compact size makes it ideal for covert installation to avoid detection and tampering. Utilizing GSM/GPRS and IP communication together with GPS technology ensures inexpensive, yet reliable and fluent communications together with efficient remote vehicle tracking.</p>		
<b>Complimentary Equipment</b>			
<b>Harness</b>			
NAME	DESCRIPTION	PART NUMBER	PICTURE
<b>Full Vehicle Harness</b>	<p>The full wiring harness, used for an installation of the Compact unit in the vehicle.</p>	<p>711-00196</p>	
<b>Relay Set</b>	<p>A standard automotive relay (P/N: 711-20000) with its socket (P/N: 711-20023). Designed to adapt between unit's output and a device in the vehicle (immobilizer, siren etc).</p>	<p>711-20000 711-20023</p>	







## Compact Security Catalog & Accessories





NAME	DESCRIPTION	PART NUMBER	PICTURE
Fuse and Housing	Protective fuse (3Amp).	710-00001	
Distress Button	Push Button, used for connection to unit's input. Can serve as a distress button for example, or as a Voice call control button.	711-20001	
<b>Back Up Batteries</b>			
Rechargeable Li-ion Batteries. 2 x 3.7v	Rechargeable internal backup battery, designed to supply power to the unit in case when the main battery of the vehicle is disconnected or completely drained. Typical capacity: 720 mAh	711-20051	
<b>Antennas</b>			
GPS receiver module	A standard Cellocator GPS receiver (SiRFIII chipset). Supplied with 3 meters cable, non-water resistant (dedicated for indoor installation). Can be supplied sealed (per request) Cable length can be supplied by request (standard 3m).	813-22720	








## Compact Security Catalog & Accessories

NAME	DESCRIPTION	PART NUMBER	PICTURE
<b>Accessories</b>			
<b>Cellocator™ Handsfree Kit</b>	A new handsfree kit (delivering superior voice quality) bundled with a matching keypad enables I-Call (information), B-Call (breakdown) and E-Call (emergency) services delivered to fleets as well as car manufactures!	712-20016	
<b>Dallas Kit</b>	Coded keys with matching receiver that enable immobilizations and driver-recognition applications for both security and fleet services. Includes 2 keys and one cradle/reader.	712-20015	
<b>Cross Plug and Cable</b>	DB9 (F) to DB9 (F) cross over plug (null modem), for connection of unit to COM port of PC using programming cable p/n 711-20078	711-20055	
<b>RJ45-DB9</b>	RJ45 – DB9(m) programming cable to connect to a COM port of a PC. Needs cross plug p/n 711-20055 to work correctly	711-00078	

## Compact Security Catalog & Accessories

NAME	DESCRIPTION	PART NUMBER	PICTURE
<b>Field Trouble Shooting Tools</b>			
<b>Vehicle Simulator Device (Tester)</b>	This device simulates the basic activities that occur in a vehicle (like Door Open, Ignition On/Off and so on) and indicates the status of the vehicle's various devices (Siren, Blinkers and so on).	715-10010	
<b>Simulator Cable</b>	The wiring harness that connects the simulator device to the Cellocator unit. The harness provides an interface to every one of Cellocator unit's I/O and communication ports	711-00135	
<b>KeyLok USB Dongle (Software protection key)</b>	KeyLok USB Dongle (Hardware Against Software Piracy) is a plug that connects to the testing computer's serial or USB port, protecting Cellocator's proprietary software and firmware against illicit use.	711-30015	
<b>Pi Cable</b>	This 4 connector pi-shaped cable is designed for trouble shooting the terminal modem side.	711-00009	



## Compact Security Catalog & Accessories

NAME	DESCRIPTION	PART NUMBER	PICTURE
<b>Communication Logging Cable</b>	A "spy cable", which, together with the Cellocator Logger software records the activities of the unit's microcontroller and GSM modem, enabling troubleshooting.	711-00039	
<b>Adaptors for Communication Logging Cable</b>		711-00038	
<b>Signal Simulator</b>	Signal simulator is a tool designed to simulate vehicle alarm system. Used to test the correlation input feature of the unit.	715-11000	
<b>GPS Simulator Cable</b>	This cable is connected to the unit and the testing computer, and by means of the GPS simulator software (included) it emulates the activity of GPS navigation in a vehicle.	711-00051	
<b>USB to RS-232 Serial Adapter</b>	USB to RS-232 Serial Adapter allows data transfer from a USB port to a serial port whenever the computer does not have a conventional RS-232 9-pin serial port.	711-30016	



Cellocator Division  
Pointer Telocation Ltd.

## Compact Security Catalog & Optional Accessories

NAME	DESCRIPTION	PART NUMBER	PICTURE
<b>Optional Accessories (not included in the basic evaluation kit)</b>			
<b>MDT860</b>	Mobile Data Terminal, allowing text messaging with the driver. The MDT includes wire harness and a flexible suction windscreen mount.	715-32000	
<b>BT Adaptor</b>	A Blue Tooth adaptor for unit's COM port, adding a BT interface to Cellocator unit.	K060-015	
<b>Enfora GSM1308 Terminal Modem Kit (optional)</b>	Terminal Modem kit is an optional component of the Cellocator's Evaluation Kit and should be ordered separately. This modem is to be connected to the PC serving as a Communication server for the purpose of establishing SMS communication with the unit or for initiating dialup connection to GPRS. The kit contains the modem, a cellular antenna, a power adaptor and a communication cable.	610-01308	