



POINTER



Cellocator Division
Pointer Telocation Ltd.

CELLOCATOR™ 370-50 EVALUATION KIT



sales@pointer.com

Ordering No.: K139-017



POINTER





Cellocator Division
Pointer Telocation Ltd.

CELLOCATOR™ 370-50 EVALUATION KIT






NAME	DESCRIPTION	PICTURE
Cellocator™ 370-50 GS72030393D	<p>The Cellocator™ 370-50 incorporates the features of the Compact Security with enhanced security capabilities such as multi IO ports and full alarm system capabilities.</p> <p>With hundreds of programmable parameters including various immobilization methods approved by insurance companies, incorporating car alarm features, advanced driver behavior analysis, tow detection, Geo-Fence, driver identification, accident detection, connection to MDT (Mobile Data Terminal), and interface with comfort car remote control.</p> <p>Utilizing GSM/GPRS and IP communication together with GPS technology ensures inexpensive, yet reliable communications together with efficient remote vehicle tracking.</p> <p>The Cellocator™ 370-50 offers security and fleet service providers and their customers with optimum solutions in coverage, lowest cost tracking, easy installation and limitless functionality.</p>	

Complimentary Equipment

Harness			
NAME	DESCRIPTION	PART NUMBER	PICTURE
Full Vehicle Harness	The full wiring harness, used for an installation of the Compact unit in the vehicle	711-00109 711-00110	
HF Adaptor (Harness)	Harness, used for an installation of the Hands Free unit.	711-00197	







CELLOCATOR™ 370-50 EVALUATION KIT

NAME	DESCRIPTION	PART NUMBER	PICTURE
Relay Set	A standard automotive relay (P/N: 711-20000) with its socket (P/N: 711-20023). Designed to adapt between unit's output and a device in the vehicle (immobilizer, siren etc).	711-20000 711-20023	
Fuse and Housing	Protective fuse (3Amp).	710-00001 710-00002	
Distress Button	Push Button, used for connection to unit's input. Can serve as a distress button for example, or as a Voice call control button.	711-20001	
Antennas			
GPS receiver module	A standard Cellocator GPS receiver (SiRFIII chipset). Supplied with 3 meters cable, non-water resistant (dedicated for indoor installation). Can be supplied sealed (per request) Cable length can be supplied by request (standard 3m).	813-52A20	
External GSM Antenna	External GSM antenna with 3m cable.	701-10009	








CELLOCATOR™ 370-50 EVALUATION KIT

NAME	DESCRIPTION	PART NUMBER	PICTURE
Back Up Battery			
Backup Battery	6v, 1.2 Ah, sealed lead acid (SLA) backup battery.	711-20060	
Accessories			
Cellocator™ Handsfree Kit	A new Hands Free kit (delivering superior voice quality) bundled with a matching keypad enables I-Call (information), B-Call (breakdown) and E-Call (emergency) services delivered to fleets as well as car manufactures!	712-20016	
Dallas Kit	Coded keys with matching receiver that enable immobilizations and driver-recognition applications for both security and fleet services. Includes 2 keys and one cradle/reader.	712-20015	
Siren SR 105A	A siren, used for feedback and signaling.	711-20004	



CELLOCATOR™ 370-50 EVALUATION KIT

NAME	DESCRIPTION	PART NUMBER	PICTURE
Programming Cable	Harness Programming	711-00006	
Vehicle Simulator Device (Tester)	This device simulates the basic activities that occur in a vehicle (like Door Open, Ignition On/Off and so on) and indicates the status of the vehicle's various devices (Siren, Blinkers and so on).	715-10000	
Simulator Cable	The wiring harness that connects the simulator device to the Cellocator unit. The harness provides an interface to every one of Cellocator unit's I/O and communication ports.	711-00111	
KeyLok USB Dongle (Software protection key)	KeyLok USB Dongle (Hardware Against Software Piracy) is a plug that connects to the testing computer's serial or USB port, protecting Cellocator's proprietary software and firmware against illicit use.	711-30015	
Pi Cable	This 4 connector pi-shaped cable is designed for troubleshooting the terminal modem side.	711-00009	







POINTER



Cellocator Division
Pointer Telocation Ltd.

CELLOCATOR™ 370-50 EVALUATION KIT

NAME	DESCRIPTION	PART NUMBER	PICTURE
Communication Logging Cable	A "spy cable", which, together with the Cellocator Logger software records the activities of the unit's microcontroller and GSM modem, enabling troubleshooting.	711-00039	
Signal Simulator	Signal simulator is a tool designed to simulate vehicle alarm system. Used to test the correlation input feature of the unit.	715-11000	
GPS Simulator Cable	This cable is connected to the unit and the testing computer, and by means of the GPS simulator software (included) it emulates the activity of GPS navigation in a vehicle.	711-00051	
USB to RS-232 Serial Adapter	USB to RS-232 Serial Adapter allows data transfer from a USB port to a serial port whenever the computer does not have a conventional RS-232 9-pin serial port.	711-30017 711-00224	






POINTER



Cellocator Division
Pointer Telocation Ltd.

CELLOCATOR™ 370-50 EVALUATION KIT

NAME	DESCRIPTION	PART NUMBER	PICTURE
Optional Accessories (not included in the basic evaluation kit)			
MDT860	Mobile Data Terminal, allowing text messaging with the driver. The MDT includes wire harness and a flexible suction windscreen mount.	715-32000	
BT Adaptor	A Blue Tooth adapter for unit's COM port, adding a BT interface to Cellocator unit.	K060-015	
Enfora GSM1308 Terminal Modem Kit (optional)	Terminal Modem kit is an optional component of the Cellocator's Evaluation Kit and should be ordered separately. This modem is to be connected to the PC serving as a Communication server for the purpose of establishing SMS communication with the unit or for initiating dialup connection to GPRS. The kit contains the modem, a cellular antenna, a power adaptor and a communication cable.	610-01308	





POINTER



Cellocator Division
Pointer Telocation Ltd.

CELLOCATOR™ 370-50 EVALUATION KIT

NAME	DESCRIPTION	PART NUMBER	PICTURE
Sensors (not included in the basic evaluation kit)			
Temperature Sensor	Enables temperature monitoring measurements in different compartments chilled.	AR-0187	
Fuel Sensor	Enables fuel monitoring consumption - connecting the analogue input of the devices.	AR-0191	
Accident Sensor	Enables accident/crash detection by triggering upon forward/backward impact of above 8g, or side impact of above 3g (adjustable sensitivity). Features false-alarm proof software.	711-20117	