



POINTER



Cellocator Division
Pointer Telocation Ltd.

COMPACT OLYMPIC EVALUATION KIT



sales@pointer.com

Ordering No.: K001-005 TETRA



POINTER



Cellocator Division
Pointer Telocation Ltd.

COMPACT OLYMPIC EVALUATION KIT

NAME	DESCRIPTION	PICTURE	
Compact Olympic EX63400823G	The Cellocator™ Olympic is an innovative integrated fleet-management unit with superior location, tracking, event-driven reporting, logging, and security capabilities. Its uniquely compact size makes it ideal for covert installation to avoid detection and tampering. Utilizing an external modem for an IP communication over almost any communication platform (like GPRS, TETRA, ASTRO, CDMA 1X, iDEN, CDPD) together with GPS technology ensures inexpensive, yet reliable and fluent communications together with efficient remote vehicle tracking.		
Complimentary Equipment			
Harness			
NAME	DESCRIPTION	PART NUMBER	PICTURE
Full Vehicle Harness	The full wiring harness, used for an installation of the Compact unit in the vehicle	711-00060	
Relay Set	A standard automotive relay (P/N: 711-20000) with its socket (P/N: 711-20023). Designed to adapt between unit's output and a device in the vehicle (immobilizer, siren etc).	711-20000 711-20023	







POINTER







Cellocator Division
Pointer Telocation Ltd.

COMPACT OLYMPIC EVALUATION KIT

NAME	DESCRIPTION	PART NUMBER	PICTURE
Fuse and Housing	Protective fuse (3Amp).	710-00001 710-00002	
Distress Button	Push Button, used for connection to unit's input. Can serve as a distress button for example, or as a Voice call control button.	711-20001	
Cross Plug and Cable	DB9 (F) to DB9 (F) cross over plug (null modem), for connection of unit to COM port of PC using programming cable p/n 711-20078.	711-20055	
Accessories			
Dallas Kit	Coded keys with matching receiver that enable immobilizations and driver-recognition applications for both security and fleet services. Includes 2 keys and one cradle/reader.	712-20015	



COMPACT OLYMPIC EVALUATION KIT

NAME	DESCRIPTION	PART NUMBER	PICTURE
Back Up Batteries			
Backup Battery	Rechargeable external 6v sealed lead acid backup battery, designed to supply power to the unit in case when the main battery of the vehicle is disconnected or completely drained. Typical capacity: 1.2 Ah.	711-20060	
Field Trouble Shooting Tools			
Vehicle Simulator Device (Tester)	This device simulates the basic activities that occur in a vehicle (like Door Open, Ignition On/Off and so on) and indicates the status of the vehicle's various devices (Siren, Blinkers and so on).	715-10000	
Simulator Cable	The wiring harness that connects the simulator device to the Cellocator unit. The harness provides an interface to every one of Cellocator unit's I/O and communication ports.	711-00114	
KeyLok USB Dongle (Software protection key)	KeyLok USB Dongle (Hardware Against Software Piracy) is a plug that connects to the testing computer's serial or USB port, protecting Cellocator's proprietary software and firmware against illicit use.	711-30015	






POINTER



Cellocator Division
Pointer Telocation Ltd.

COMPACT OLYMPIC EVALUATION KIT

NAME	DESCRIPTION	PART NUMBER	PICTURE
Pi Cable	This 4 connector pi-shaped cable is designed for trouble shooting the terminal modem side.	711-00009	
GPS Simulator Cable	This cable is connected to the unit and the testing computer, and by means of the GPS simulator software (included) it emulates the activity of GPS navigation in a vehicle.	711-00051	
USB to RS-232 Serial Adapter	USB to RS-232 Serial Adapter allows data transfer from a USB port to a serial port whenever the computer does not have a conventional RS-232 9-pin serial port.	711-30017 711-00224	
Harness		711-0103	




POINTER



Cellocator Division
Pointer Telocation Ltd.

COMPACT OLYMPIC EVALUATION KIT

NAME	DESCRIPTION	PART NUMBER	PICTURE
Optional Accessories (not included in the basic evaluation kit)			
MDT860	Mobile Data Terminal, allowing text messaging with the driver. The MDT includes wire harness and a flexible suction windscreen mount.	715-32000	
BT Adaptor	A Blue Tooth adapter for unit's COM port, adding a BT interface to Cellocator unit.	K060-015	