



POINTER



Cellocator Division
Pointer Telocation Ltd.

COMPACT SECURITY EVALUATION KIT



sales@pointer.com

Ordering No.: K062-011






POINTER



Cellocator Division
Pointer Telocation Ltd.

COMPACT SECURITY EVALUATION KIT

NAME	DESCRIPTION	PICTURE	
Compact Security GT660007B-TR3N GE660007B-ER3N	<p>The Cellocator™ Compact Security is an innovative integrated Car Alarm and fleet management unit with superior location, tracking, event driven reporting, logging, and security capabilities. Its uniquely compact size makes it ideal for covert installation to avoid detection and tampering. Utilizing GSM/GPRS and IP communication together with GPS technology ensures inexpensive, yet reliable and fluent communications together with efficient remote vehicle tracking.</p>		
Complimentary Equipment			
Harness			
712-00196			
NAME	DESCRIPTION	PART NUMBER	PICTURE
Full Vehicle Harness	<p>The full wiring harness, used for an installation of the Compact unit in the vehicle.</p>	<p>711-00196</p>	
Relay Set	<p>A standard automotive relay (P/N: 711-20000) with its socket (P/N: 711-20023). Designed to adapt between unit's output and a device in the vehicle (immobilizer, siren etc).</p>	<p>711-20000 711-20023</p>	







POINTER



Cellocator Division
Pointer Telocation Ltd.

COMPACT SECURITY EVALUATION KIT

NAME	DESCRIPTION	PART NUMBER	PICTURE
Fuse and Housing	Protective fuse (3Amp).	710-00001 710-00002	
Distress Button	Push Button, used for connection to unit's input. Can serve as a distress button for example, or as a Voice call control button.	711-20001	
Back Up Batteries			
Rechargeable Li-ion Batteries. 2 x 3.7v	Rechargeable internal backup battery, designed to supply power to the unit in case when the main battery of the vehicle is disconnected or completely drained. Typical capacity: 720 mAh	711-20051	
Antennas			
GPS receiver module	A standard Cellocator GPS receiver (SiRFIII chipset). Supplied with 3 meters cable, non-water resistant (dedicated for indoor installation). Can be supplied sealed (per request) Cable length can be supplied by request (standard 3m).	813-22720	







POINTER



Cellocator Division
Pointer Telocation Ltd.

COMPACT SECURITY EVALUATION KIT

NAME	DESCRIPTION	PART NUMBER	PICTURE
Accessories			
Cellocator™ Handsfree Kit	A new handsfree kit (delivering superior voice quality) bundled with a matching keypad enables I-Call (information), B-Call (breakdown) and E-Call (emergency) services delivered to fleets as well as car manufactures!	712-20016	
Dallas Kit	Coded keys with matching receiver that enable immobilizations and driver-recognition applications for both security and fleet services. Includes 2 keys and one cradle/reader.	712-20015	
Cross Plug and Cable	DB9 (F) to DB9 (F) cross over plug (null modem), for connection of unit to COM port of PC using programming cable p/n 711-20078	711-20055	
RJ45-DB9	RJ45 – DB9(m) programming cable to connect to a COM port of a PC. Needs cross plug p/n 711-20055 to work correctly	711-00078	







POINTER



Cellocator Division
Pointer Telocation Ltd.

COMPACT SECURITY EVALUATION KIT

NAME	DESCRIPTION	PART NUMBER	PICTURE
Field Trouble Shooting Tools			
Vehicle Simulator Device (Tester)	This device simulates the basic activities that occur in a vehicle (like Door Open, Ignition On/Off and so on) and indicates the status of the vehicle's various devices (Siren, Blinkers and so on).	715-10010	
Simulator Cable	The wiring harness that connects the simulator device to the Cellocator unit. The harness provides an interface to every one of Cellocator unit's I/O and communication ports	711-00077	
KeyLok USB Dongle (Software protection key)	KeyLok USB Dongle (Hardware Against Software Piracy) is a plug that connects to the testing computer's serial or USB port, protecting Cellocator's proprietary software and firmware against illicit use.	711-30015	
Pi Cable	This 4 connector pi-shaped cable is designed for trouble shooting the terminal modem side.	711-00009	








POINTER



Cellocator Division
Pointer Telocation Ltd.

COMPACT SECURITY EVALUATION KIT

NAME	DESCRIPTION	PART NUMBER	PICTURE
Communication Logging Cable	A "spy cable", which, together with the Cellocator Logger software records the activities of the unit's microcontroller and GSM modem, enabling troubleshooting.	711-00039	
Adaptors for Communication Logging Cable		711-00038	
Signal Simulator	Signal simulator is a tool designed to simulate vehicle alarm system. Used to test the correlation input feature of the unit.	715-11000	
GPS Simulator Cable	This cable is connected to the unit and the testing computer, and by means of the GPS simulator software (included) it emulates the activity of GPS navigation in a vehicle.	711-00051	
USB to RS-232 Serial Adapter	USB to RS-232 Serial Adapter allows data transfer from a USB port to a serial port whenever the computer does not have a conventional RS-232 9-pin serial port.	711-30017 711-00224	






POINTER



Cellocator Division
Pointer Telocation Ltd.

COMPACT SECURITY EVALUATION KIT

NAME	DESCRIPTION	PART NUMBER	PICTURE
Optional Accessories (not included in the basic evaluation kit)			
MDT860	Mobile Data Terminal, allowing text messaging with the driver. The MDT includes wire harness and a flexible suction windscreen mount.	715-32000	
BT Adaptor	A Blue Tooth adapter for unit's COM port, adding a BT interface to Cellocator unit.	K060-015	
Enfora GSM1308 Terminal Modem Kit (optional)	Terminal Modem kit is an optional component of the Cellocator's Evaluation Kit and should be ordered separately. This modem is to be connected to the PC serving as a Communication server for the purpose of establishing SMS communication with the unit or for initiating dialup connection to GPRS. The kit contains the modem, a cellular antenna, a power adaptor and a communication cable.	610-01308	
Accident Sensor	Enables accident/crash detection by triggering upon forward/backward impact of above 8g, or side impact of above 3g (adjustable sensitivity). Features false-alarm proof software.	711-20017	